PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

IT

(51) International Patent Classification 6: B08B 3/02, A47L 11/00

A1

(11) International Publication Number:

WO 99/59740

(43) International Publication Date: 25 November 1999 (25.11.99)

(21) International Application Number:

PCT/IT99/00136

(22) International Filing Date:

17 May 1999 (17.05.99)

(30) Priority Data:

PD98A000127 PD98A000269 20 May 1998 (20.05.98)

13 November 1998 (13.11.98) IT

(71) Applicant (for all designated States except US): IDROBASE S.N.C. [IT/IT]; Via dell'Industria, 25, I-35010 Borgoricco

(72) Inventors; and

- (75) Inventors/Applicants (for US only): FERRARESE, Bruno [IT/IT]; Via dell'Industria, 25, I-35010 Borgoricco (IT). GAZZIGNATO, Bruno [IT/IT]; Via dell'Industria, 25, I-35010 Borgoricco (IT).
- (74) Agent: BENETTIN, Maurizio; Via Sorio, 116, I-35141 Padova (IT).

(81) Designated States: AU, CA, JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published

With international search report.


Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

In English translation (filed in Italian).

(54) Title: MULTIPURPOSE HYDRO-MACHINE WITH VARIOUSLY ASSEMBLED MODULES

(57) Abstract

The invention is a new multipurpose machine for cleaning surfaces and floors in general provided with an independent basic module which can be assembled with more modules endowed with various fittings according to the different user's needs. The basic module is provided with wheels (1.3), supports for the nozzles, tanks and force pump assembly (4) for the nozzles. The other modules consist of a boiler assembly (3.2) and heating exchanger, a feedbox (3.4) for taking and mixing the sand with the water under pressure; an intaking liquids-vacuum cleaner assembly, the tanks (3.5, 8) for additives and detergents, specific nozzles (5); a floor cleaning assembly with vacuum cleaner provided with rotating brushes (6) and floor-cleaning bar (7).



BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM AT AU AZ BA BB	Albania Armenia Austria Australia Azerbaijan Bosnia and Herzegovina	es fi fr ga	Spain Finland France	LT LU	Lithuania	SK	Slovakia
AT AU AZ BA BB	Australia Azerbaijan	GA		8.71			
AZ BA BB	Azerbaijan			LU	Luxembourg	SN	Senegal
BA BB			Gabon	LV	Latvia	SZ	Swaziland
BA BB		GB	United Kingdom	MC	Monaco	TD	Chad
		GE	Georgia	. MD	Republic of Moldova	TG	Togo
BE	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
ВЈ	Benin	1E	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA (Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF (Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG (Congo	KE	Kenya	NL	Netherlands	YU	Yugostavia
CH :	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM (Cameroon		Republic of Korea	PL	Poland		
CN (China	KR	Republic of Korea	PT	Portuga!		
CU (Cuba	KZ	Kazakstan	RO	Romania		
C7.	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE (Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

1

MULTIPURPOSE HYDRO-MACHINE WITH VARIOUSLY ASSEMBLED MODULES

DESCRIPTION

This patent relates to the field of industrial and/or professional cleaning machines and particularly regards hydro-machines, in the case in point hydro-cleaning machines, hydro-sandblasting machines, floor cleaning machines, vacuum cleaner and the like.

Cleaning machines with particular functions and facilities are being used according to the surface and to the kind of dirty to be clean.

Hydro- cleaning machines shoot an high pressure water jet and are essentially provided with a motor pump and a nozzle to localize the water jet under pressure.

Hydro-cleaning machine are used for removing simple dirty such as mud, stratified dust, strong but superficial organic substance from particularly delicate surfaces.

Hydro-sandblasting machines shoot a water jet under pressure mixed with sand. The water in pressure, thanks to the Venturi effect, intakes the sand from its tanks and conveys it at an high speed on the surface to be clean. The hydro-sandblasting machines are particularly used for removing the deeper paint from the surfaces, and for abrading stone materials, etc.

Other kinds of hydro-cleaning machines are provided with devices for heating water and/or adding a variable concentration of additives, solvents, chemical agents to the water during their use.

5

10

15

20

10

15

20

25

4

Each kind of machine above mentioned can carry out specific functions i.e. for example, some hydro-cleaning machines are provided with devices for being turned into hydro-sandblasting machines without heating the water and without adding soaps or solvents.

In any case, the hydro-machines require some additional devices or often a further distinct unit for heating and using water, for adding additives, using sand, etc.

Small firms especially craft firms often buy only hydro-cleaning machines and then, during their activity, they need hydro-sandblasting machines, and further hydro-cleaning machines possibly arranged for using simultaneously chemical solvents or detergents. The firms are therefore compelled to buy a machine with all requirements they need or to buy distinct units to couple with the machines already in their possession. The costs for buying additional machines isn't often justified by the bulk of work to carry out.

In order to overcome to the above mentioned drawbacks a new type of multipurpose hydro-machine has been designed and implemented.

The new hydro-machine is provided with several modules variously assembled to a main module or basic module, including a frame, a main body with a pump, some supports for the nozzles and a tank to which some devices such as an heating module, a module with feedbox or with tank for the sand, a module with

10

15

20

attachments particularly suitable for centers, a floor cleaning module with brushes and an intaking module for liquids can be added by means of quick coupling devices.

The basic module is provided with wheels whereas the other modules can either be provided with wheels, in order to aid their movements and discharge their weight to the ground, or be lacking of wheels, in this case at least a module with wheels is added.

Essentially, the modules are divided in a basic or main module and in various modules coupling with the main one and carrying the other complementary parts, wherein the quick coupling system allow to easily coupled and uncoupled the various modules with rapidity and ease.

The basic or main module consists of a structural frame with handle or handgrip, provided with a lower plane with lateral wheels. Some supports are fixed to the structural frame for putting the nozzles back when are not utilized, the force pump which sends water or air to the nozzles is fixed to the frame as well. On the same plane it is possible to insert a battery with suitable features for the electrical feeding of said force pump, while the structural part of the frame, opposite to the handle or the handgrip, is arranged for being coupled with the structural frame of one of modules following described.

It is possible to fixed a second plane over the lower plane. One or more tanks are positioned or solidly fixed on each plane or only

4

on the lower one. Said tanks contain, for example, water and an additive such as a detergent.

A first additional module consists of a frame with a plane provided with two wheels wherein the frame shows some ends suitable for being coupled with the structural frame of the main module. On said additional module an heating assembly consisting of an heating exchanging chamber and a burner is housed.

A second additional module consists of a structure frame with a plane provided with two wheels wherein the frame shows some ends suitable for being coupled with the structural frame of the main module. On said additional module, a feedbox containing sand or other equivalent products is housed.

A third additional module consists of a frame with a plane provided with two wheels wherein the frame shows some ends suitable for being coupled with the structural frame of the main or basic module. On said additional module a vacuum cleaner assembly, an intaking liquids assembly and one or more tanks containing additives and/or detergents, some particular nozzles such as nozzle-foam and/or nozzle-floor are lodged.

A fourth additional module consists of a floor cleaning assembly which includes a vacuum cleaner provided with brushes with vertical axis and rear floor cleaning bar and wherein said module is provided with two wheels whereas the frame is endowed with ends for being coupled with the structural frame of the main or

25 basic module.

-4

5

10

10

4

The various modules are provided with jacks and connection ducts to join together nozzles, pumps, heating exchangers, tanks and the other parts besides the various electrical connections.

The various modules can be assembled with the basic module according to the needs and the functions required.

The basic hydro-cleaning module can be assembled with other modules in order to obtain an heating hydro-cleaning machine or a sandblasting machines, or an hydro-cleaning machines for particular operations, or a floor cleaning machines, simply adding the proper module to the main one.

The hydro-machine consists preferably of a main or basic module provided with a frame, a main body with pump and supports for the nozzles and the tanks to which is possible to join, by means of quick coupling devices, several modules variously assembled:

- 15 a module with heater
 - a sandblasting module with feedbox or tank for the sand,
 - a module intaking dust or liquids,
 - a floor-cleaning module with brushes and intaking liquids device,
 - a toolholder module (for brooms, sponges, detergents),
- a moquettes-washing module.

The main or basic module consists of a structural frame with handle or handgrip endowed with a lower plane and three or four lateral wheels. The wheels have two different diameters that is the rear wheel/s are smaller than the front ones and are positioned so

10

15

20

25

4)

that the rear wheels are raised from the ground when the basic module is joined to one of the other modules.

The structural frame is internally provided with some housings for putting back the nozzles when are not used, the force pump, and a possible battery for the electrical feeding of the pump, whereas the structural part of the frame, opposite to the handle or the handgrip, is arranged for coupling the structural frame with one of the other modules.

Particularly, the coupling between the basic module and an additional module assures a quick and safe connection and reduce the coupling and uncoupling operations as little as possible. The junction is possible by means of one or more coupling pins. The various electrical, water and pneumatic connections are possible by means of the coupling of the two modules. Actually, appropriate electrical connectors and pneumatic seal unions are positioned on the surface or on the junction edges between the modules.

A further innovative part of the new hydro-machine is that the covering or the case of the basic module instead of doing the function of simply covering the basic module can be utilized, in a different arrangement and combination, both as a covering of the basic module and as a covering of each additional module.

Thus, it is possible to assembly the main hydro-cleaning module with the other modules obtaining, simply adding the suitable module to the main one, an heating hydro-cleaning machine, or a

10

15

20

sandblasting machine, or an hydro-cleaning machine for particular purposes, or a floor-cleaning machine.

The new hydro-machine as described above, solves completely all the problems cited in the introduction. In fact, it is possible to obtain an hydro-machine with various and amplified functions simply removing the covering or the case of the main module, coupling the main module with an additional one and positioning the covering or the case previously removed on said hydro-machine. All that can be obtained by means of few and easy operations carried out quickly and with safe working.

Each additional modules consists of a framework with plane provided with two wheels and edges or fittings for coupling the structural frame with the main module. The additional module is endowed with jacks and connection ducts in order to put together nozzles, pumps, heating exchangers, tanks and other parts besides the various electrical connections.

An heating assembly consisting of a burner with heating exchanger is housed on the first additional module (warm water). Said module allows the main module to work as an hydro-thermocleaning machine.

A feedbox containing sand or other equivalent products is housed on the second additional module (hydro-sandblasting) by means of which the basic module is able to become an hydro-sandblasting.

A vacuum cleaner assembly, a module for intaking liquids, one or more tanks for additives and/or detergents, and some particular nozzles such as nozzle-foam and/or nozzle-floor are positioned on the third additional module (vacuum cleaner module/ module for intaking liquids).

A floor cleaning assembly including a vacuum cleaner provided with brushes with vertical axis and rear floor cleaning bar are positioned on the fourth additional module (floor-cleaning).

Some housings holding bottles and containers for detergents and some supports for the brushes, sponges and brooms are lodged on

Some brushes, sprayers, tanks for dirty cleaning water, and other fittings for cleaning moquettes are mounted on the sixth additional module

the fifth additional module.

The new hydro-machine as described above can overcome the drawbacks cited in the introduction. In fact, a small firm can buy, at a first stage, only the main module and then acquire the other modules according to the practical needs. The hydro-machine which results has exactly the features desired and moreover consists of only a body easy to transport and to move without removing more objects not connected together.

The attached tables show by way of example, but not limitative, an embodiment of the invention.

Figures 1a, 1b, 1c, show three views, as an example, of the basic module consisting of a structural frame (1.1) with the lower plane (1.2) and wheels (1.3), and a force pump for the water (4).

Figures 2a, 2b, 2c, show three views, as a further example, of the basic module consisting of a structural frame (1.1) with the lower plane (1.2), the wheels (1.3), the force pump for the water (4) and the tank (2).

- 5 Figures 3a, 3b, 3c, show three views of an additional module consisting of a structural frame (3) with wheels (3.1) supporting a boiler (3.2) with burner (3.3) for the heating.
 - Figures 4a, 4b, 4c, show three views of the second additional module consisting of a structural frame (3) with wheels (3.1) supporting a feedbox (3.4).
 - Figures 5a, 5b, 5c, show three views of a further additional module consisting of a structural frame (3) with wheels (3.1) supporting an intaking assembly (3.7), the tank (3.5) and provided with nozzles (5).
- Figures 6a, 6b, 6c, show three views of a further additional module consisting of a structural frame (3) with wheels (3.1) provided with floor cleaning assembly with brushes (6) and the relating motor (6.1), with cleaning bar (7) and the tank for cleaning liquid (8).
- Figure 7 shows one of the possible assembling wherein the basic module is joined to the heating assembly.
 - Figures 8 15 show the various junction phases between the basic module and an additional module:
 - figure 8 shows the basic module to be used as independent device;

figure 9 shows the basic module with the covering of the tanks for the additives or detergents removed;

figures 10 and 11 show two removed coverings;

figures 12 and 13 show the covering positioned on the additional module;

figure 14 shows the additional module joined to the basic module; figure 15 shows the coverings, previously removed, positioned on the basic module and on the additional module joined together.

These are sufficient schematic indications to allow an expert person to put the project into effect; consequently, in tangible application, some variations may be made without affecting the substance of the innovative concept.

Therefore, with reference to the above description and to the enclosed tables, the following claims are put forth.

10

15

20

25

CLAIMS

- 1. Multipurpose hydro-machine characterized in that it comprises a main or basic module which is independent and can be assembled with various modules provided with different fittings, and wherein said basic module is endowed with wheels, supports for the nozzles, tanks and force pump for the nozzles.
- 2. Hydro-machine, according to claim 1, characterized in that the basic module is provided with four wheels of which two are small and two big, and wherein said small wheels are set in the rear position of the basic module, and wherein said small wheels are raised when the basic module is coupled with the additional module.
- 3. Hydro-machine, according it claims 1, 2, characterized in that it comprises a module to be joined with the main module, said module is provided with a boiler assembly and an heating exchanger and the relating devices for electrical and water connection, etc.
- 4. Hydro-machine, according to claim 1, 2, characterized in that it comprises a further module provided with wheels to be joined to the main or basic module, said module is provided with a feedbox for the sand which is taken and mixed with the water under pressure for the Venturi effect.
- 5. Hydro-machine, according to claims 1, 2, characterized in that it comprises a further module provided with wheels to be coupled with the main module, said module is endowed with vacuum

cleaner, intaking assembly for liquids, tanks for the additives and/or detergents, particular nozzles like nozzle-foam and nozzle-floor.

- 6. Hydro-machine, according to claims 1, 2, characterized in that it comprises another module provided with wheels consisting of a floor-cleaning assembly and vacuum cleaner, moreover, said module comprises a brushes assembly with vertical axis and a rear floor cleaning bar, and it is also provided with some edges for the union with the main or basic module.
- 7. Hydro-machine, according to claims 1 6, characterized in that the coverings of the main module are movable and can be removed from the main module and applied on any additional module provided with the corresponding coupling device, obtaining continuity between the structures of the main module and the additional one.
 - 8. Multipurpose hydro-machine, according to claim 7, characterized in that it is provided with quick mechanical, water and electrical connections between the basic module and the additional one.

1/11





Fig. 16






Fig. 1a

Fig. 1c





Fig. 2b








Fig. 2a


Fig. 2c

























5/11











6/11










Fig. 6c

7/11





Fig. 7

8/11








fig.

9/11




ig. 10




iq. 11


10/11














710.15

INTERNATIONAL SEARCH REPORT

Intel onal Application No PCT/IT 99/00136

A. CLASSII IPC 6	FICATION OF SUBJECT MATTER B08B3/02 A47L11/00		·
According to	o International Patent Classification (IPC) or to both national class	fication and IPC	
	SEARCHED		
Minimum do IPC 6	cumentation searched (classification system followed by classific B08B A47L B24C	ation symbola)	
	tion searched other than minimum documentation to the extent the		
Electronic d	ata base consulted during the international search (name of data	base and, where practical, search term	ns used)
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the	relevam passages	Relevant to claim No.
X	US 5 263 223 A (FIEGEL ET AL) 23 November 1993 (1993-11-23) column 2, line 15 - line 39 column 4, line 52 - column 6, figures	line 33;	1
Y A			3 5,8
Υ	DE 44 11 040 C (STARKE BRÜCKE IMPORT-EXPORT GMBH) 13 April 1995 (1995-04-13) abstract; figures		3
Α	abstract, rigures		1
		-/	
X Furt	her documents are listed in the continuation of box C.	Patent family members an	e listed in annex.
"A" docum consid	ategories of cited documents: ent defining the general state of the art which is not dered to be of particular relevance document but published on or after the international	"T" later document published after to priority date and not in conflicted to understand the princip invention." "X" document of particular relevance."	lict with the application but le or theory underlying the
which citatio "O" docum	date ent which may throw doubts on priority claim(s) or is cited to establish the publication date of another in or other special reason (as specified) ent referring to an oral disclosure, use, exhibition or means	cannot be considered novel or involve an inventive step wher "Y" document of particular relevanc cannot be considered to involve document is combined with on ments, such combination bein	cannot be considered to the document is taken alone se; the claimed invention we an inventive step when the se or more other such docu—
later t	ent published prior to the international filing date but han the priority date claimed	in the art. "&" document member of the same	
	actual completion of the international search O September 1999	Date of mailing of the internation of the internati	onal search report
	mailing address of the ISA	Authorized officer	
	European Patent Office, P.B. 5818 Patentiaan 2 NL – 2280 HV Rijawijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Van der Zee,	W

Form PCT/ISA/210 (second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

Interr Inel Application No
PCT/IT 99/00136

		PC1/11 99/00136
<u> </u>	ation) DOCUMENTS CONSIDERED TO BE RELEVANT	
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 4 934 017 A (KENT) 19 June 1990 (1990-06-19) abstract column 1, line 8 - line 32 column 4, line 16 - column 5, line 1; figures	1,5
Α	i rigui es	2,6
Y	DE 297 20 383 U (ELEKTRA BECKUM AG) 12 February 1998 (1998-02-12) the whole document	1,5
Α .	WO 97 49528 A (FRIENDLY MACHINES LTD. ET AL) 31 December 1997 (1997-12-31) page 3, line 2 - line 12 page 7, line 22 - line 26 page 10, line 13 - page 11, line 2 page 16, line 3 - line 7; figures	1,2,5,6,
Α	DE 34 45 200 A (COLUMBUS-PROFIVAC GMBH) 19 June 1986 (1986-06-19) abstract page 15, line 1 - line 7 page 20, line 5 - line 12 page 21, line 1 - line 3 page 21, line 21 - page 22, line 17 page 24, line 21 - page 25, line 10 page 33, line 13 - page 35, line 8; figures	1,2,5,6,
A	US 3 704 811 A (HARDEN, JR) 5 December 1972 (1972-12-05) column 6, line 63 - column 7, line 67; figures 4-7	1,4,8

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

in and in

INTERNATIONAL SEARCH REPORT

PCT/IT 99/00136

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5263223	Α	23-11-1993	NONE	
DE 4411040	С	13-04-1995	NONE	
US 4934017	Α	19-06-1990	NONE	
DE 29720383	U	12-02-1998	EP 0917912 A	26-05-1999
WO 9749528	Α	31-12-1997	AU 3105097 A EP 0920367 A	14-01-1998 09-06-1999
DE 3445200	Α	19-06-1986	NONE	
US 3704811	Α	05-12-1972	NONE	

Form PCT/ISA/210 (petern family annex) (July 1992)

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

BLACK BORDERS

IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

FADED TEXT OR DRAWING

BLURRED OR ILLEGIBLE TEXT OR DRAWING

SKEWED/SLANTED IMAGES

COLOR OR BLACK AND WHITE PHOTOGRAPHS

GRAY SCALE DOCUMENTS

LINES OR MARKS ON ORIGINAL DOCUMENT

REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

IMAGES ARE BEST AVAILABLE COPY.

OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.